

IJ532 – Arctik™ Bright White Photo Canvas 350gsm

Product	Description	A 350gsm Matte, smooth textured bright white 100% cotton canvas with inkjet recep-tive coating. The cotton is completely seedless and the surface finish quite smooth, making it ideal for photographic reproductions. The use of pigment ink provides a long-lasting image which can be further enhanced by application of a water-based lacquer or varnish. Easy to stretch and fold with good crack resistance. Please note that Matte Black ink is not fully water resistant, so care is advised when handling.
	Compatibility	Water based pigment ink (dye ink will fade quickest and is least water resistant)
Application	Indoor Usage	Art Reproduction, Commercial Décor, Home Décor, Hotels, Gifts, High Street print-on-de-mand, On-line print-on-demand, Museums and Galleries, Studio Photography If required, use a suitable water based lacquer or varnish to provide additional protec-tion from UV fading and excessive moisture. Allow a minimum of 12 hours for the ink to dry before applying the lacquer and take special care not to smudge the ink.
	Outdoor	Not recommended
	Lamination	Compatible with liquid varnish coatings. Lamination may be applied over printed surfaces finished with liquid varnish, subject to suitability testing for the specific varnish and lami-nate combination.
	Printing	10-30°C, 30-65% RH, select highest print quality for optimal result
	Method	Printed canvas to be used with stretcher bar frames and wall mounted
Structure	Base material	Textile, 100% cotton with a microporous coating
	Surface	Matte bright white finish
Technical	Weight	350 gsm
	Thickness	450 micron
	Gloss (60°)	n/a
	Opacity	> 96%
	Optical brighteners	Yes
	White Point	L: 95.7 a: 1.8 b: -5.1
Storage	Temperature	10-30°C
	Humidity	30-65% RH
Size	Roll (12m length)	432mm, 610mm, 914mm, 1067mm, 1118mm, 1270mm, 1524mm (2" core)
	Sheets	n/a
Notes	Samples	A4 and 2m samples available on request.
	Specification	This data sheet does not constitute a guaranteed specification and is given in good faith. Users of this product are encouraged to evaluate under the specific application and envi-ronmental conditions to which the product will be used.