

IJ700 – Stickytex™ Adhesive Wall Fabric 220gsm

Product	Description	A 200gsm bright white polyester fabric with an inkjet receptive coating and reposition-able self-adhesive back. It can be removed and repositioned without damaging the wall and leaves no residue. Will not rip or wrinkle and is water resistant with pigment and Latex ink. User must check wall surface for suitability and is not recommended for use near heat sources.
	Compatibility	Dye and Pigment water-based inks
	Environmental	Phthalate free, PVC free
Application	Indoor Usage	Ideal for bespoke wallpaper designs, exhibition graphics, large murals, wall stickers
	Outdoor	Short term outdoor use but this product must be laminated to protect against any moisture. Edges must be overlapped by at least 5mm to provide adequate protection
	Method	To increase product performance please note the following: • The wall should be smooth, clean and free of any cleaning contaminants. • Allow 4 weeks for a freshly painted wall to fully cure otherwise there is a risk of bubbles forming under the surface. • Washable hardwearing paints and low energy plastics will have certain non-stick properties (please consider a test sample first). • The use of a wall primer (e.g. Zinsser) will provide more consistent results. • The recommended room environment for application is 20-35°C and non-humid. Optimum adhesion is reached after 72-96 hours. • Below 10°C the adhesive will not stick easily (or be more difficult to remove). • Above 37°C the adhesive will gradually soften and start to lose its grip making for easier removal. • Strong sunlight, overexposure to UV curing or high drying temperatures will reduce the adhesive performance* • To remove the product, peel slowly at warmer temperatures (20-35°C).
Structure	Base material	Textile, 100% woven polyester (150 denier)
	Surface	Matte white finish
	Adhesive	Acrylic based adhesive, repositionable
	Release liner	Siliconised PE paper 120 gsm
Technical	Weight	220 gsm (without the Release liner)
	Thickness	165 microns (without the Release liner)
	Opacity	> 85%
	White point	L: 92.5 a: 2.8 b: -9.8
	Stability	Good
	Adhesion strength	N/a
Storage	Temperature / Humidity	10-30°C at 30-65% RH
Size	Roll (30m length)	610mm, 1067mm (3" core)
Notes	Samples	A4 and 2m samples available on request.
	Specification	This data sheet does not constitute a guaranteed specification and is given in good faith. Users of this product are encouraged to evaluate under the specific application and environmental conditions to which the product will be used.