

IJ703 – Graffiti™ Smooth Matte Wallpaper 180gsm

Product	Description	A 180gsm Matte, smooth natural white non-woven wallpaper with a premium porous inkjet coating that provides both instant drying and a high degree of image protection. The coating provides for excellent colour reproduction, and the paper is designed for good dimensional stability and wet strength performance. To be applied using a standard paste-the-wall wallpaper adhesive. To further enhance the print life a liquid lami-nate can be applied prior to pasting. Fire rating: C-s1, d0.
	Compatibility	Water-based Pigment and Latex inks
	Environmental	PVC free
		Fire classification : C-s1, d0 (ISO EN 13501-1 ; 2007)
Application	Indoor Usage	Ideal for bespoke wallpaper designs, Exhibition Graphics, Large Murals.
	Outdoor	Not recommended
	Method	For optimal adhesion the wall must be smooth, dry and clean. For ease of use an application temperature of 15 - 25°C is recommended. The wallpaper paste may not be compatible with certain products which have non-stick properties. This includes some of the hard wearing, high acrylic content paints, if in doubt check a small sample first. When sticking to a painted surface, you should allow a minimum of 4 weeks for the paint to thoroughly dry (off-gas) before hanging.
Structure	Base material	Non-woven wallpaper
	Surface	Smooth matte finish
	Adhesive	Hang using a standard wallpaper paste
Technical	Weight	180 gsm
	Thickness	340 microns
	Gloss (60°)	n/a
	Opacity	> 93%
	White point	L: 95.2 a: -0.3 b: 0.7
	Adhesion strength	N/a
Storage	Temperature / Humidity	10-30°C at 30-65% RH
Size	Roll (30m length)	610mm, 1067mm (3" core)
Notes	Samples	A4 and 2m samples available on request.
	Specification	This data sheet does not constitute a guaranteed specification and is given in good faith. Users of this product are encouraged to evaluate under the specific application and environmental conditions to which the product will be used.

IJ703 – Graffiti™ Smooth Matte Wallpaper 180gsm

Intended use	Interior wallcovering
Structure	Non-woven wallpaper with a matte coating that is printable with pigmented water-based inks
Storage	The product should be kept in the original packaging (cardboard box and PE bag). Storage conditions of 10-30°C and 30-65% RH are recommended.
Health & safety	According to our experience, no damage to health has ever been reported or is to be expected, if used as intended.
Fire hazard	Wearing of self-contained breathing apparatus is recommended because, as with organic materials in general, formation of carbon monoxide (CO) and carbon dioxide (CO ₂) could occur. Reaction to fire performance rating: C,s1-d0 VOC emissions: A+
Waste disposal	Small quantities may be disposed of with normal household waste. Larger quantities should be disposed of according to local or national government regulations. We recommend to contact your responsible waste management company.
Regulatory information	This product is not subject to the regulations on transport and labelling that apply to dangerous substances. This product is in compliance with RoHS directive 2011/65/EU. The product is in compliance with REACH Regulation (EC) No 1907/2006. According to REACH this product is an article. Substances of very high concern (SVHC, candidate list of the 2017-01-12), in concentrations above 0,1 wt-%, are not used in the production.
Additional Information	None
Notes	This data sheet does not constitute a guaranteed specification and is given in good faith. Users of this product are encouraged to evaluate under the specific application and environmental conditions to which the product will be used.