

TM327 – Clear Window Cling Film 150mic

Product	Description	A 150micron Gloss, transparent monomeric vinyl static cling film with a standard coating that provides fast drying and a high degree of image protection. The film is supplied on a thick lay flat paper liner. Designed primarily for interior window graphics where the graphic is to be viewed from inside. Large graphics are best applied using a 'wet' technique.
	Compatibility	Solvent, Eco-Solvent, Latex and UV curable inks
	Environmental	The product does not contain substances included in the "Candidate List of Substances of very high concern for authorisation" by ECHA.
Application	Indoor	Designed for use on glass surfaces for up to 3 years. When used on other glossy surfaces such as acrylics, Perspex, polyester etc. some ink residue may be transferred over time if the printed side is placed in contact.
	Outdoor	Suitable for outdoor use, up to one year under vertical conditions (-20°C to +50°C)
	Method	Ensure window surface is properly clean prior to application. Application temperature +10°C to +40°C
Structure	Base material	Monomeric PVC cling film
	Appearance	Clear Glossy finish
	Backing sheet	White, single sided clay-coated paper, 180gsm
Technical	Weight	180 gsm (without release liner)
	Thickness	150 microns (without release liner)
	Opacity	Transparent
	Adhesion	< 0.08 N/25mm (FTM 1) on clean glass
	Stability	< 0.4mm (FTM14)
Storage	Temperature	15-25°C
	Humidity	40-60% RH
Size	Roll (50m length)	1372mm (3" core)
	Sheets	n/a
Notes	Samples	A4 and 2m samples available on request.
	Specification	This data sheet does not constitute a guaranteed specification and is given in good faith. Users of this product are encouraged to evaluate under the specific application and environmental conditions to which the product will be used.