

TM328 – White Window Cling Film 150mic

Product	Description	A 170micron Gloss, white monomeric vinyl static cling film with a standard coating that provides fast drying and a high degree of image protection. The film is supplied on a thick lay flat paper liner. Designed primarily for interior window graphics where the graphic is to be viewed from inside. Large graphics are best applied using a 'wet' technique.
	Compatibility	Solvent, Eco-Solvent and UV curable inks
Application	Indoor	Suitable for use on smooth glossy surfaces, flat panels or slightly curved structures. Ideal for short term presentation and advertising panels. The cling works on both sides so making it perfect for window display graphics viewed from inside or out. Leaves no residue and is easy to remove and re-use. Indoor use 3 years.
	Outdoor	Suitable for outdoor use, up to one year under vertical condition (-20°C to 50°C)
	Method	Ensure window surface is properly clean prior to application. Application temperature 10-40°C
Structure	Base material	Electrostatic PVC film, monomeric
	Appearance	White Glossy finish
	Backing sheet	Paper with one side clay coated, 180gsm
Technical	Weight	184 gsm (without the backing sheet)
	Thickness	150 microns (without the backing sheet)
	Opacity	Good
	White point	L: 94.0 a: -0.3 b: -2.0
	Stability	< 0.4mm shrinkage (FTM 14)
Storage	Temperature	15-25°C
	Humidity	40-65% RH
Size	Roll (50m length)	1372mm (3" core)
	Sheets	n/a
Notes	Samples	A4 and 2m samples available on request.
	Specification	This data sheet does not constitute a guaranteed specification and is given in good faith. Users of this product are encouraged to evaluate under the specific application and environmental conditions to which the product will be used.