

TM331 – Crystal Clear Hi-Tac Window Film 120mic

Product	Description	A 120micron, optically clear polyester film with a semi-permanent crystal-clear adhesive for absolute clarity. Can be applied wet or dry and leaves no residue when re-moved. The coating allows maximum ink weights for bright saturated colours and is water and scratch resistant. Ideal for reverse printing. Dimensionally stable so will not shrink like PVC.
	Compatibility	Solvent, Eco-Solvent, Latex and UV curable inks
Application	Indoor	Specifically designed for use on Retail Window Advertising, Residential Interiors, Glass Partitions and Cubicles
	Outdoor	Not recommended for outdoor use
	Lamination	Optional, however the printed image must be completely dry before lamination, a minimum of 48 hours is recommended for optimal results. (Polyester laminate)
Structure	Method	Ensure window surface is properly clean prior to application. For larger installations, wet mount is recommended. Application conditions 15-30°C, 30-60% humidity.
	Base material	Ultra clear polyester
	Appearance	Clear gloss finish with a translucent matte backing liner
	Adhesive	Repositionable adhesive that leaves no residue when moved
Technical	Backing sheet	60 micron translucent film with a matte back
	Weight	185 gsm
	Thickness	150 microns (including adhesive)
	Opacity	Transparent
	Stability	Excellent
Storage	Temperature	10-25°C
	Humidity	40-60% RH
Size	Roll (30m length)	1270mm (3" core)
	Sheets	n/a
Notes	Samples	A4 and 2m samples available on request.
	Specification	This data sheet does not constitute a guaranteed specification and is given in good faith. Users of this product are encouraged to evaluate under the specific application and environmental conditions to which the product will be used.