

TM620 – Clear Vinyl Permanent Adhesive 100mic

Product	Description	A 100micron Gloss, transparent monomeric vinyl with an ink receptive coating and a permanent clear water-based adhesive with thick paper release liner. The coating provides an excellent colour gamut with good durability. Ideal for indoor use or up to 3 years outdoor use and can be laminated for extra protection against sunlight and abrasion. B1 flame retardant.
	Compatibility	Solvent, Eco-Solvent, Latex* and UV Curable inks * Maximum recommended temperature of 80 °C
Application	Indoor	Suitable for a variety of uses on flat or slightly curved surfaces
	Outdoor	Suitable for short-term use (up to 3 months) without lamination
	Lamination	Suitable for lamination to extend product life
Structure	Base material	Soft PVC, monomeric, transparent
	Surface	Glossy finish
	Adhesive	Permanent water-based adhesive
	Release liner	Siliconised kraft paper, 135gsm
Technical	Weight	140 gsm (without release liner)
	Thickness	100 microns (without release liner)
	Gloss (60°)	n/a
	Opacity	Transparent
	Adhesion strength	14 N/25mm (after 24 hours on glass - Finat 1) with low initial tack.
	Stability	Shrinkage < 0.2mm (Finat FTM 14)
	White Point	n/a
Storage	Temperature	10-25°C
	Humidity	30-65% RH
Size	Roll (50m length)	760m, 1370mm, 1600mm (3" core)
	Sheets	n/a
Notes	Samples	A4 and 2m samples available on request.
	Specification	This data sheet does not constitute a guaranteed specification and is given in good faith. Users of this product are encouraged to evaluate under the specific application and environmental conditions to which the product will be used.