

TM631 – TACLite™ Repositionable Polypropylene S/A 170mic

Product	Description	A 170micron Satin, white polypropylene with an ink receptive coating and easy-to-remove TACLite adhesive with thick paper release liner. Ideal for smooth surfaces such as glass and laminated surfaces, a great alternative to cling film. Ideal for removable stickers with a thick paper liner for ease of cutting, easy to apply and remove. Edge tear resistant with a good colour gamut. Not suitable for painted walls or textured surfaces.
	Compatibility	Solvent, Eco-Solvent and UV Curable inks
	Environmental	PVC free
Application	Indoor	Suitable for a variety of uses on smooth, flat or slightly curved surfaces
	Outdoor	Short-term outdoor use
	Lamination	Suitable for lamination to extend product life
Structure	Base material	White polypropylene
	Surface	Satin finish
	Adhesive	Repositionable water-based acrylic adhesive
	Release liner	Siliconised kraft paper, 140gsm
Technical	Weight	170 gsm (without release liner)
	Thickness	210 microns (without release liner)
	Gloss (60°)	n/a
	Opacity	> 94%
	Optical brighteners	Medium ($\Delta\Delta b$: 5.6)
	CIE Whiteness	82
	White Point	L: 97.2 a: 0.8 b: - 3.1
	Adhesion strength	< 1 N/25mm (after 24 hours on glass - Finat FTM 1)
	Stability	Good
Storage	Temperature	10-30°C
	Humidity	30-65% RH
Size	Roll (30m length)	1067, 1270, 1372mm (3" core)
	Sheets	n/a
Notes	Samples	A4 and 2m samples available on request.
	Specification	This data sheet does not constitute a guaranteed specification and is given in good faith. Users of this product are encouraged to evaluate under the specific application and environmental conditions to which the product will be used.