

TM633 – Textured Direct Print R10 Floor Vinyl 150mic

Product	Description	A 150micron Matte, textured bright white monomeric vinyl with an ink receptive coating and a removable adhesive backing with air-release structured paper liner. The coating provides for good colour reproduction and the R10 anti-slip surface makes it ideal for short-term indoor use in public spaces such as shopping centres and super-markets. Good scratch resistance with no lamination required. Fire rating: C-s1, d0.
	Compatibility	Solvent, Eco-Solvent and UV Curable inks
	Fire rating	C-s1-d0 (EN13501-1: 2007 +A1 2009)
	Slip rating	R10 (DIN 51130: 2014)
Application	Indoor	Suitable for a variety of uses on smooth, flat or slightly curved surfaces
	Outdoor	Short-term outdoor use
	Temperature	Application temperature from 10°C to 40°C
	Lamination	Not required
Structure	Base material	PVC, monomeric, white
	Surface	Textured finish
	Adhesive	Repositionable water-based acrylic pressure sensitive, moderate tack
	Release liner	Siliconized kraft paper, structured air-release.
Technical	Weight	n/a
	Thickness	150 microns (including adhesive)
	Gloss (60°)	n/a
	Opacity	n/a
	White Point	L: 94.3 a: 0.5 b: - 3.6
	Adhesion strength	Moderate tack, removable
	Stability	n/a
Storage	Temperature	10-25°C
	Humidity	30-65% RH
Size	Roll (50m length)	1370mm (3" core)
	Sheets	n/a
Notes	Samples	A4 and 2m samples available on request.
	Specification	This data sheet does not constitute a guaranteed specification and is given in good faith. Users of this product are encouraged to evaluate under the specific application and environmental conditions to which the product will be used.