

TM635 – Print2Floor™ Textured Vinyl 150mic

Product	Description	A 180micron Matte, heavily textured white monomeric vinyl with an ink receptive coating and a removable adhesive backing with air-release structured paper liner. The coating provides for good colour reproduction and the R10 anti-slip surface makes it ideal for short-term indoor use in public spaces such as shopping centres and super-markets. Good scratch resistance with no lamination required.
	Compatibility	Solvent, Eco-Solvent and UV Curable inks
	Fire rating	C-s1-d0 (EN13501-1: 2007 +A1 2009)
	Slip rating	R10 (DIN 51130: 2014)
Application	Indoor	Can be applied to Direct Print Indoor Floor Graphics, POS Signage, Wall Graphics Not suitable for some types of PVC flooring, ceramic tiles or natural stone. Please ask for a sample to properly evaluate the product suitability.
	Outdoor	Not recommended for outdoor use
	Temperature	Application temperature from 10°C to 40°C
	Lamination	Not required
Structure	Base material	PVC, monomeric, white
	Surface	Textured finish
	Adhesive	Repositionable water-based acrylic pressure sensitive, moderate tack
	Release liner	Siliconized kraft paper, structured air-release.
Technical	Weight	n/a
	Thickness	160 microns (including adhesive)
	Gloss (60°)	n/a
	Opacity	n/a
	White Point	L: 94.3 a: 0.5 b: - 3.6
	Adhesion strength	Moderate tack, removable
	Stability	n/a
Storage	Temperature	10-25°C
	Humidity	30-65% RH
Size	Roll (50m length)	1370mm (3" core)
	Sheets	n/a
Notes	Samples	A4 and 2m samples available on request.
	Specification	This data sheet does not constitute a guaranteed specification and is given in good faith. Users of this product are encouraged to evaluate under the specific application and environmental conditions to which the product will be used.