

TM639 – StickyDot™ White Gloss - Bubble Free S/A 130mic

Product	Description	A 130micron Glossy, bright white monomeric vinyl with an ink receptive coating and a repositionable acrylic adhesive with a thick paper release liner. The coating allows for heavier ink weights, provides a photo realistic finish with excellent scratch resistance and is suitable for short to medium-term outdoor use. The StickyDotadhesive tech-nology is designed to allow the user to easily install the graphic on a variety of smooth surfaces without bubbles forming, thus avoiding the need for a wet installation tech-nique.
	Compatibility	Solvent, Eco-Solvent and UV Curable inks
	Fire rating	C-s1-d0 (EN13501-1: 2007 +A1 2009)
	Slip rating	R10 (DIN 51130: 2014)
Application	Indoor	For use of Window decoration, POS, Window advertising, Indoor and Outdoor Frontlit display.
	Outdoor	Short-term outdoor use
	Temperature	Printing temperature from 15°C to 30°C
	Lamination	Can be laminated to protect printed image
Structure	Base material	White PVC film
	Surface	Glossy finish
	Adhesive	Permanent adhesive, initially repositionable
	Release liner	Siliconized kraft paper
Technical	Weight	n/a
	Thickness	140 microns (including adhesive)
	Gloss (60°)	n/a
	Opacity	n/a
	White Point	L: 95.1 a: - 0.6 b: - 0.7
	Adhesion strength	Moderate tack, removable
Storage	Temperature	10-25°C
	Humidity	30-65% RH
Size	Roll (50m length)	1370mm (3" core)
	Sheets	n/a
Notes	Samples	A4 and 2m samples available on request.
	Specification	This data sheet does not constitute a guaranteed specification and is given in good faith. Users of this product are encouraged to evaluate under the specific application and environmental conditions to which the product will be used.