

TM762 – Camouflage™ Pre-Pasted Wallpaper 220gsm

Product	Description	A 220gsm Satin-matte, softly textured, natural white non-woven wallpaper with a premium ink receptive coating and pre-pasted back. The premium coating provides for rapid drying, high ink weights and a wide colour gamut with good resistance to wear. The paper has high opacity for good coverage and excellent wet strength resistance. Immersing the wallpaper in water activates the dry pre-pasted adhesive making it the same consistency as standard wallpaper paste. Fire rating: C-s1, d0 and VOC: A+
	Environmental	PVC free
		VOC emissions: A+ (EN ISO 16000)
		Reaction to fire classification: D-s1,d0 (EN 13501-1 : 2007)
	Compatibility	Solvent, Eco Solvent, Latex, UV curable
Application	Indoor	The printed product is water resistant and lamination is not usually required
	Outdoor	Not suitable for outdoor use
	Method	Immersing the wallpaper in a water trough for a maximum of 15 seconds activates the adhesive, making it the same consistency as standard wallpaper paste. Change the water frequently depending on length of drop, (e.g. every 5 drops)
Structure	Base material	Non-woven wallpaper
	Surface	Smooth satin finish
	Adhesive	Permanent, water-based adhesive (water activated)
Technical	Weight	220 gsm
	Thickness	325 micron
	Gloss (60°)	n/a
	Opacity	> 91%
	Optical brighteners	None
	CIE Whiteness	70
	White Point	L: 96.0 a: -0.4 b: 4.4
	Stability	Excellent
Storage	Temperature	10-30°C
	Humidity	30-65% RH
Size	Roll (50m length)	760mm, 1067mm, 1270mm (3" core)
Notes	Samples	A4 and 2m samples available on request.
	Specification	This data sheet does not constitute a guaranteed specification and is given in good faith. Users of this product are encouraged to evaluate under the specific application and environmental conditions to which the product will be used.