

TM772 – Stickytex (s) Opaque Adhesive Wall Fabric 220gsm

Product	Description	A 220gsm Satin-matte, white finely woven fabric with an ink receptive coating and a removable adhesive back with paper release liner. The coating provides rapid drying and a wide colour gamut with good resistance to wear. The grey repositionable adhesive provides additional covering power to achieve 95% blackout, it can be removed and repositioned without damaging the wall and leaves no residue.
	Environmental	Phthalate free, PVC free
	Compatibility	Eco Solvent, Latex*, Resin, UV curable*
Application	Indoor	Wall design, exhibition graphics, advertising, signage
	Outdoor	The printed product is water resistant and lamination is not usually required.
	Method	To increase product performance please note the following: • The wall should be smooth, clean and free of any cleaning contaminants. • Allow 4 weeks for a freshly painted wall to fully cure otherwise there is a risk of bubbles forming under the surface. • Washable hardwearing paints and low energy plastics will have certain non-stick properties (please consider a test sample first). • The use of a wall primer (e.g. Zinsser) will provide more consistent results. • The recommended room environment for application is 20-35°C and non-humid. Optimum adhesion is reached after 72-96 hours. • Below 10°C the adhesive will not stick easily (or be more difficult to remove). • Above 37°C the adhesive will gradually soften and start to lose its grip making for easier removal. • Strong sunlight, overexposure to UV curing or high drying temperatures will reduce the adhesive performance* • To remove the product, peel slowly at warmer temperatures (20-35°C).
Structure	Base material	100% woven polyester fabric
	Surface	Matte finish
	Adhesive	Acrylic, low-tack pressure-sensitive adhesive, repositionable
	Release Liner	Siliconised paper, double sided PE coated, 160gsm, 150 microns
Technical	Weight	220 gsm (without liner)
	Thickness	200 microns (without liner)
	Opacity	> 95%
	Optical brighteners	Low
	White Point	L: 91.7 a: 0.5 b: - 3.4
	Stability	Good
Storage	Temperature	10-25°C (keep boxed and away from direct sunlight)
	Humidity	30-65% RH
Size	Roll (30m length)	760mm, 1067mm and 1372mm (3" core)
Notes	Samples	A4 and 2m samples available on request.
	Specification	This data sheet does not constitute a guaranteed specification and is given in good faith. Users of this product are encouraged to evaluate under the specific application and environmental conditions to which the product will be used.