

## DTF PRINTER

## **FEATURES**

- 2 and 4-head configuration available for faster printing speed and greater efficiency
- Supports CMYK+W printing with a high-quality print finish
  - Fluorine rubber pressure roller reduces static build-up and ensures accurate paper feeding
  - Intelligent take-up system ensures material is rolled up neatly for easy use
  - Anti-collision system protects printhead from damage when encountering obstacles
  - Liftable capping station enables height adjustment of printheads for ease of maintenance



SPECIFICATION			
Printer Model	60cm DTF Printer	Transmission Interface	Gigabit LAN
Printhead	2pcs Epson I3200-A1	RIP Software	FlexiPRINT RIP
Printing Speed	6pass 12-15m <sup>2</sup> /h 8pass 9-11m <sup>2</sup> /h	Image Format	BMP, JPG, TIFF, EPS, PDF
Printing Width	60cm/24inch	Computer System	Windows XP/Win7/Win8/Win10
Ink	CMYK+W Pigment Ink	Power Supply	220V, 50/60 HZ, 10A 350W
Print Media	DTF Film	Ideal Operating Environment	TEMP.: 10°C-38°C
Heating System	Front and Back Independent Heater		Humidity: 40%-70%
		Dimensions	189cm x 74cm x 85cm
		Weight	220kg

Inkled



InkTec Europe

Bulford House Supergas Industrial Estate Downs Road Witney OXON OX29 0SZ

T: +44 (0)1993 862770 dtf@inkteceu.com